



Terrain Attack R/T

Designed for the true off-road enthusiast, the Terrain Attack R/T is engineered to conquer the toughest terrains with ease, delivering exceptional performance and durability, without compromising on-road comfort.

2 SIDEWALL DESIGNS. SAME OPTIMAL PERFORMANCE.

The Terrain Attack R/T features two unique sidewall designs, allowing for further vehicle customization.

SIDEWALL 1

A dynamic stepped V-pattern, along with integrated Amp "A" tread blocks, generates numerous gripping edges along the sidewall.

SIDEWALL 2

A rugged, pocketed block design with varying heights combines style and exceptional off-road performance.



50K MILE
TREAD LIFE
WARRANTY



MANUFACTURERS
LIMITED
LIFETIME
WARRANTY



OFF-ROAD TRACTION

Stone ejectors channel away water, mud, rocks, & other debris to maintain maximum grip and performance.



ALL-SEASON PERFORMANCE

Large, open shoulder blocks greatly improve off-road traction and enhance grip in extreme weather conditions.



LONG-LASTING DURABILITY

Staggered sidewall provides protection against punctures and abrasions in harsh environments.



WIDE CONTACT CENTER PATCH

The versatile, hybrid tread patterns features a wide contact center patch that increases surface coverage on any terrain, while providing longer tread life and a quiet and smooth ride on the road.



VARIABLE PITCH TREAD PATTERN

Innovative tread design optimizes road contact, reduces road noise, and enhances overall performance

PRODUCT SPECIFICATIONS

TIRE SIZE	PART NO.	LOAD RANGE	TREAD DEPTH (1/32")	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	MAX LOAD SINGLE	MAX PRESS. SINGLE	APPROVED RIM WIDTH RANGE (IN)
17"								
P265/70R17	265-7017AMP/RTSL	SL	14.0	31.7	10.7	2535LBS	44PSI	7.0-9.0(8.0)
LT285/70R17	285-7017AMP/RTC	C	16.4	32.8	11.5	2755/2535LBS	50PSI	7.5-9.5(8.5)
35X12.50R17LT	35-125017AMP/RTE	E	18.9	34.8	12.5	3640LBS	65PSI	8.0-10.5(10.0)
20"								
LT285/55R20	285-5520AMP/RTE	E	16.4	32.6	11.7	3305/3000LBS	80PSI	8.5-10.0(9.0)
33X12.50R20LT	33-125020AMP/RTE	E	18.9	32.8	12.5	2600LBS	65PSI	8.5-11.0(10.0)
LT305/55R20	305-5520AMP/RTF	F	16.4	33.5	12.4	3640/3305LBS	80PSI	9.0-11.0(9.5)
35X12.50R20LT	35-125020AMP/RTE	E	18.9	34.8	12.5	3195LBS	65PSI	8.5-11.0(10.0)
35X12.50R20LT	35-125020AMP/RTF	F	18.9	34.8	12.5	3640LBS	80PSI	8.5-11.0(10.0)
22"								
33X12.50R22LT	33-125022AMP/RTE	E	18.9	32.8	12.5	2270LBS	65PSI	8.5-11.0(10.0)
33X12.50R22LT	33-125022AMP/RTF	F	18.9	32.8	12.5	2600LBS	80PSI	8.5-11.0(10.0)
35X12.50R22LT	35-125022AMP/RTE	E	18.9	34.8	12.5	2835LBS	65PSI	8.5-11.0(10.0)
35X12.50R22LT	35-125022AMP/RTF	F	18.9	34.8	12.5	3195LBS	80PSI	8.5-11.0(10.0)
24"								
35X13.50R24LT	35-135024AMP/RTE	E	18.9	34.8	13.4	2470LBS	65PSI	11.5-13.5(11.0)
35X13.50R24LT	35-135024AMP/RTF	F	18.9	34.8	13.4	2755LBS	80PSI	11.5-13.5(11.0)
37X13.50R24LT	37-135024AMP/RTE	E	18.9	36.8	13.6	3525LBS	80PSI	9.5-12.0(11.0)
37X13.50R24LT	37-135024AMP/RTF	F	18.9	36.8	13.6	3085LBS	65PSI	9.5-12.0(11.0)
COMING SOON								
P275/55R20 XL	275-5520AMP/RTXL	XL	14.0	31.9	11.2	2601LBS	51PSI	7.5-9.5 (8.5)
38X13.50R20LT	38-135020AMP/RTE	E	18.9	37.7	13.6	3970LBS	65PSI	9.5-12.0 (11.0)
LT295/55R22	295-5522AMP/RTE	E	16.4	35.0	12.2	3640/3305LBS	80PSI	8.5-10.5 (9.5)
38X13.50R22LT	38-135022AMP/RTE	E	18.9	37.7	13.6	3750LBS	65PSI	9.5-12.0 (11.0)
38X13.50R22LT	38-135022AMP/RTF	F	18.9	37.7	13.6	3970LBS	80PSI	9.5-12.0 (11.0)
285/40R24 XL	285-4024AMP/RTXL	XL	14.0	32.9	11.4	2469LBS	51PSI	9.5-11.0 (10.0)
LT295/45R24	295-4524AMP/RTE	E	16.4	34.7	11.7	3085/2835LBS	80PSI	9.5-11.0 (10.0)
LT305/35R26	305-3526AMP/RTE	E	16.4	34.6	12.3	2205/1985LBS	65PSI	10.0-12.0 (11.0)
35X15.50R26LT	35-155026AMP/RTF	F	18.9	34.7	15.5	2835LBS	80PSI	13.0-15.5 (14.0)
38X13.50R26LT	38-135026AMP/RTF	F	18.9	37.7	13.6	3415LBS	80PSI	9.5-12.0 (11.0)



Terrain Attack A/T A

Boasts an off-road attitude with smooth on-road characteristics. Offers stable control of a variety of environments with a performance tread design featuring a multi-block pattern. Perfect for anyone seeking adventure both on and off-road.





**PERFORMANCE
TREAD DESIGN**

Unique multi-block tread design ensures smooth ride quality along with superior off road handling and grip.



**TWIN-LUG
SIDEWALL**

Sidewall designed with dual variation lug technology for greatly improved traction in all environments and all weather conditions.



**OFF-ROAD
PERFORMANCE**

The staggered tread block design was made to improve traction in loose dirt, debris and sand.



**STAGGERED
TREAD DEPTH**

Deep, stepped tread blocks channel dirt, mud, and water away from the tire in all weather conditions.

PRODUCT SPECIFICATIONS

TIRE SIZE	PART NO.	LOAD RANGE	TREAD DEPTH (1/32")	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	MAX LOAD SINGLE	MAX PRESS. SINGLE	APPROVED RIM WIDTH RANGE (IN)
17"								
LT265/70R17	265-7017AMP/CA3	E	15.5	31.7	10.7	3195LBS/2910LBS	80PSI	7.0-9
LT285/70R17	285-7017AMP/CA3	E	15.5	32.8	11.5	3195LBS/2910LBS	80PSI	7.5-9.5
LT315/70R17	315-7017AMP/CA3	E	15.5	34.4	12.7	3195LBS/2910LBS	65PSI	8.0-10.5
18"								
LT305/60R18	305-6018AMP/CA3	E	15.5	32.4	12.2	3195LBS/2910LBS	65PSI	9.0-11.0
LT305/70R18	305-7018AMP/CA3	E	15.5	34.8	12.2	3750LBS/3415LBS	65PSI	8.0-10.0
20"								
LT265/50R20	265-5020AMP/CA3	E	15.5	30.5	10.9	2680LBS/2470LBS	80PSI	8.0-9.5
LT275/55R20	275-5520AMP/CA3	D	15.5	31.9	11.2	2680LBS/2470LBS	65PSI	8.0-9.5
LT285/55R20	285-5520AMP/CA3	E	15.5	32.4	11.7	3305LBS/3000LBS	80PSI	8.0-10.0
LT305/55R20	305-5520AMP/CA3	E	15.5	33.2	12.4	3195LBS/2910LBS	65PSI	9.0-11.0
35x12.50R20LT	35-125020AMP/CA3	E	15.5	34.5	12.5	3195LBS	65PSI	8.5-11.0
37x12.50R20LT	37-125020AMP/CA3	E	15.5	36.5	12.5	3750LBS	65PSI	8.5-11.0
22"								
305/40R22	305-4022AMP/CA3	XL	13.9	31.6	12.3	2601LBS	50PSI	10.0-12.0
33x12.50R22LT	33-125022AMP/CA3	E	15.5	32.5	12.5	2270LBS	65PSI	8.5-11.0
35x12.50R22LT	35-125022AMP/CA3	E	15.5	34.5	12.5	2835LBS	65PSI	8.5-11.0



Terrain Pro A/T P


Built with a longer tread life that withstands demanding environments. Experience traction in various terrains with deep, multi-function tread grooves, while enjoying a smooth and controlled ride.





PERFORMANCE TREAD DESIGN

Stepped tread blocks allow more stable control and multidirectional sipes create greater traction in wet weather.



OFF-ROAD PERFORMANCE

Advanced compound prevents chipping and delivers a longer tread life with more consistent contact surface to deliver a smooth and controlled ride.



STEEP TREAD DEPTH

Deep grooves and rock ejectors keep tread grooves free of mud, dirt, and gravel while mitigating possible punctures



TWIN-LUG SIDEWALL

Unique "twin peaks" sidewall and open shoulder design deliver assertive performance in every condition and help evacuate water & mud for improved traction.

PRODUCT SPECIFICATIONS

TIRE SIZE	PART NO.	LOAD RANGE	TREAD DEPTH (1/32")	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	MAX LOAD SINGLE	MAX PRESS. SINGLE	APPROVED RIM WIDTH RANGE (IN)
17"								
LT265/70R17	265-7017AMP/CA2	E	15.1	31.7	10.7	3195LBS/2910LBS	80PSI	7.0-9.0
LT285/70R17	285-7017AMP/CA2	E	15.1	32.8	11.5	3195LBS/2910LBS	80PSI	7.5-9.5
LT315/70R17	315-7017AMP/CA2	E	15.1	34.4	12.7	3195LBS/2910LBS	65PSI	8.0-10.5
18"								
LT275/70R18	275-7018AMP/CA2	E	15.8	33.2	11.0	3640LBS/3305LBS	80PSI	7.0-9.0
LT285/65R18	285-6518AMP/CA2	E	15.8	32.6	11.5	3640LBS/3305LBS	80PSI	8.5-10.0
LT325/65R18	325-6518AMP/CA2	E	15.8	34.6	13.0	3860LBS/3525 LBS	65PSI	9.5-11.5
20"								
LT265/60R20	265-6020AMP/CA2	E	15.1	32.5	10.7	3195LBS/2910LBS	80PSI	8.0-9.5
LT275/55R20	275-5520AMP/CA2	D	15.8	31.9	11.2	2680LBS/2470LBS	65PSI	8.0-9.5
LT275/60R20	275-6020AMP/CA2	E	15.8	33.0	11.0	3415LBS./3085LBS	80PSI	8.0-9.5
LT275/65R20	275-6520AMP/CA2	E	15.1	34.1	11.0	3750LBS./3415LBS	80PSI	8.0-9.5
LT285/55R20	285-5520AMP/CA2	E	15.8	32.4	11.7	3305LBS/3000LBS	80PSI	8.5-10.0
LT285/60R20	285-6020AMP/CA2	E	15.1	33.5	11.5	3640LBS/3305LBS	80PSI	8.5-10.0
LT295/65R20	295-6520AMP/CA2	E	15.5	35.1	11.8	4080LBS/3750LBS	80PSI	8.5-10.5
LT305/55R20	305-5520AMP/CA2	E	15.8	33.2	12.4	3195LBS/2910LBS	65PSI	9.0-11.0
33X12.50R20LT	33-125020AMP/CA2	E	15.8	32.5	12.5	2600LBS	65PSI	8.5-11.0
35X12.50R20LT	35-125020AMP/CA2	E	15.5	34.5	12.5	3195LBS	65PSI	8.5-11.0
LT325/60R20	325-6020AMP/CA2	E	15.8	35.4	13.0	3750LBS./3415LBS	65PSI	9.5-11.5
22"								
LT285/45R22	285-4522AMP/CA2	D	15.8	32.1	11.2	2835LBS	65PSI	9.0-10.5
LT285/55R22	285-5522AMP/CA2	E	15.5	34.4	11.7	3525LBS/3195LBS	80PSI	8.5-10.0
LT295/50R22	295-5022AMP/CA2	E	15.8	33.7	12.2	3305LBS/3000LBS	80PSI	8.5-10.5
24"								
P305/35R24	305-3524AMP/CA2	XL	14.4	32.5	12.2	2469LBS	50PSI	10.0-12.0
33x12.50R24LT	33-125024AMP/CA2F	F	15.8	32.5	12.6	2095LBS	80PSI	10.5-12.5
35X12.50R24LT	35-125024AMP/CA2F	F	15.8	34.5	12.5	2755LBS	80PSI	10.0-12.0



Terrain Attack M/T A

The AMP Terrain Attack M/T is designed to perform in the most extreme conditions while offering improved grip and handling for better on-road performance. The 3-ply "A" logo sidewall provides biting edges and outstanding grip in mud, rock, sand, snow and more.





PERFORMANCE TREAD DESIGN

The deep sipes and distinct channel design significantly increase traction in wet or muddy conditions.



OFF-ROAD PERFORMANCE

The unique shoulder design features a staggered tread block that provides reliable grip in unreliable terrain and consistent traction for better on road performance.



AGGRESSIVE TREAD

The tread pattern is aggressively designed to remove mud, dirt, and debris while keeping continuous contact for superior off road traction and better on-road control.



TWIN-LUG SIDEWALL

Reinforced sidewall boasts "A" logo lug design which provides dynamic biting edges to maintain grip through the most extreme conditions or when airing down tires.

PRODUCT SPECIFICATIONS

TIRE SIZE	PART NO.	LOAD RANGE	TREAD DEPTH (1/32")	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	MAX LOAD SINGLE	MAX PRESS. SINGLE	APPROVED RIM WIDTH RANGE (IN)
17"								
35x12.50R17LT	35-125017AMP/CM2	E	19.0	34.8	12.5	3195LBS	65PSI	8.5-11.0
37x12.50R17LT	37-125017AMP/CM2	D	19.0	36.8	12.5	3525LBS	50PSI	9.0-10.5
18"								
LT285/65R18	285-6518AMP/CM2	E	19.0	32.8	11.5	3640LBS/3305LBS	80PSI	8.5-10.0
35x12.50R18LT	35-125018AMP/CM2	E	19.0	34.8	12.5	3415LBS	65PSI	8.5-11.0
20"								
LT285/55R20	285-5520AMP/CM2	E	19.0	32.6	11.7	3305/3000LBS	80PSI	8.0-10.0
LT305/55R20	305-5520AMP/CM2	E	19.0	33.5	12.4	3195LBS/2910LBS	65PSI	9.0-11.0
33x12.50R20LT	33-125020AMP/CM2	E	19.0	32.8	12.5	2600LBS	65PSI	8.5-11.0
35x11.50R20LT	35-115020AMP/CM2	E	19.5	34.8	11.4	3525LBS	80PSI	8.0-10
35x12.50R20LT	35-125020AMP/CM2	E	19.0	34.8	12.5	3195LBS	65PSI	8.5-11.0
37x13.50R20LT	37-135020AMP/CM2	E	19.0	36.8	13.6	3860LBS	65PSI	9.5-12.0
22"								
LT325/50R22	325-5022AMP/CM2	E	19.0	34.8	13.2	3305LBS	65PSI	9.5-11.5
33x12.50R22LT	33-125022AMP/CM2	E	19.0	32.5	12.5	2270LBS	65PSI	8.5-11.0
33x14.50R22LT	33-145022AMP/CM2F	F	19.0	32.7	14.5	2830LBS	95PSI	10.0-13.0
35x15.50R22LT	35-155022AMP/CM2F	F	19.0	34.7	15.5	3640LBS	80PSI	11.0-14.0
37x12.50R22LT	37-125022AMP/CM2F	F	19.5	36.8	12.5	3860LBS	80PSI	8.5-11.0
37x13.50R22LT	37-135022AMP/CM2	E	19.0	36.8	13.6	3415LBS	65PSI	9.5-12.0
24"								
33x13.50R24LT	33-135024AMP/CM2F	F	19.5	32.5	13.6	3200LBS	80PSI	9.5-12.0
35x13.50R24LT	35-135024AMP/CM2	E	19.5	34.8	15.3	2835LBS	65PSI	12.5-15
35x15.50R24LT	35-155024AMP/CM2	E	21.0	36.8	13.6	3085LBS	65PSI	9.5-12.0
37x13.50R24LT	37-135024AMP/CM2	E	19.5	37.8	15.5	3860LBS	65PSI	12.5-15
38x13.50R24LT	38-135024AMP/CM2F	E	19.5	34.8	13.4	2470LBS	65PSI	9.5-12.0
38x15.50R24LT	38-155024AMP/CM2	F	19.5	37.8	13.6	3860LBS	80PSI	9.5-12
26"								
33x13.50R26LT	33-135026AMP/CM2F	F	19.5	32.8	13.6	2755LBS	80PSI	12.5-15
35x13.50R26LT	35-135026AMP/CM2F	F	19.5	34.6	13.6	2835LBS	80PSI	11 - 13
37x13.50R26LT	37-135026AMP/CM2F	F	19.5	36.3	13.6	2835LBS	80PSI	11 - 13
38x15.50R26LT	38-155026AMP/CM2	E	19.5	37.7	15.2	3750LBS	65PSI	12.5-15
28"								
37x13.50R28LT	37-135028AMP/CM2F	F	19.5	36.8	13.6	2600LBS	80PSI	11-14